



HEAVY DUTY
PLATFORM

PRO-ZONE™



Heavy duty panels
designed for heavy traffic

PROFLOOR
PORTABLE FLOORING

MANUFACTURER
SALES
HIRE

E: info@profloor.com.au
W: www.profloor.com.au

- Stadiums & concerts
- Portable roadways
- Mining industry
- Vehicle access
- Building sites

STADIA



MILITARY



CAR PARKS



LOADING PLATFORMS



CONSTRUCTION



EASY TO INSTALL



FEATURES

- Easy to install lightweight panels with twist-lock fasteners
- Load-dispersing to accommodate heavy machinery
- Protects sports turf profiles
- Skid-resistant surface
- Rugged, reusable and recyclable

USES

- Temporary access enabling construction of stages for concerts and events in stadia
- Work areas where heavy loads need to be distributed e.g. crane platforms
- Portable roadways for heavy vehicles
- Military operations
- Golf course maintenance

INDUSTRIES

- Major events
- Stadium operators
- Mining
- Construction
- Military

TECHNICAL DATA

MATERIAL	High strength thermoplastic.
UV STABILISED	Protected against excessive colour fading and deterioration.
MAT SIZE	1.49m ² . Usable surface of 1.15m ² . Thickness: 6.35cm.
WEIGHT	Each mat weighs approx. 23kgs.
SURFACE	Skid-resistant surface helps ensure traction for people and equipment. The over-hanging lip system provides a continuous barrier between ground and work surface, reducing the chance of slipping and movement.
LOAD FACTOR	Can support compressive loads of up to 3100kPa on firm subsurface.
CONNECTION	Four pre-installed twist-lock fasteners lock each Pro-Zone™ mat securely into place with a simple 90° turn. A waist-high T-handled wrench is specially designed to speed installation and removal while reducing physical strain.
CLEANING	May be swept, mopped, scrubbed and pressure-washed. Resistant to most common detergents and cleaning fluids.
SERVICE LIFE	Between 8-10 years (under normal conditions).
INSTALLATION	Mats can be installed in a few hours by unskilled workers with no experience with the Pro-Zone™ system. In addition, the mats can be easily assembled into many different configurations.
INSTALLATION RATE	Approx. 40m ² /hour/man.
COLOURS	Slate Grey, Desert Tan, custom colours available on request at additional cost.
ACCESSORIES	Ramp accessory to improve transition from ground to mat surface.