



GARAGE
FLOORING

PRO-FLOOR® MR



Tough garage flooring
withstands petrol & oil spills

PROFLOOR
PORTABLE FLOORING

MANUFACTURER
SALES
HIRE



E: info@profloor.com.au
W: www.profloor.com.au

- Pit garage floors
- Pathways
- Marquee floors
- Merchandising & display areas
- Transporter annexes

PRO-FLOOR® MR

THE IDEAL FLOOR SOLUTION FROM GO-KARTS TO F1

PIT GARAGE FLOORS



MAJOR EVENTS



PATHWAYS



TROLLEY JACKS



AVAILABLE IN A RANGE OF COLOURS OR MATCH TO YOUR CORPORATE COLOURS.



DISPLAY AREAS



FEATURES

- Portable, lightweight flooring that's easy to install and store
- Designed to accommodate uneven ground
- Slip-resistant with self-draining features to provide a clean, dry, safe surface
- Heavy duty without breakable joining pieces, withstands trolley jacks, air jacks, axle stands
- Customised flooring to match corporate colours for added branding impact and create borders, numbers, words etc
- Rolls up for compact storage in transporters

USES

- Pit garage floors
- Pathways and roadways
- Marquee floors
- Merchandising and display areas
- Transporter annexes

INDUSTRIES

- Motor racing
- Motor events and exhibitions

TECHNICAL DATA

MATERIAL	Recyclable polypropylene copolymer. Specific engineering-grade material for high impact, toughness, flexibility and resilience.
UV STABILISED	Treated against excessive colour fading and deterioration.
FIRE RATING	NFP92-501 Epiradiateur Test M4. AS/NZS 1530.3-1999: Ignitibility = 15, Spread of Flame = 2, Heat Evolved = 2, Smoke Developed = 4.
WORKING TEMP	-10°C to +50°C.
TREAD SIZE	Unassembled, each tread is 310mm long, 88mm wide and 17mm high. These connect length and widthwise to form segments of any size, 39.6 assembled treads per m ² .
WEIGHT	Approx. 110gm per tread, 4.3kg per m ² .
LOAD FACTOR	Static - 29,000kg/m ² on firm surface.
STORAGE	42m ² /cu.m. in rolls, 56m ² /cu.m. flat sections.
CLEANING	May be swept, mopped, scrubbed and pressure-washed. Resistant to most common detergents and cleaning fluids. Pro-Floor® MR cleaning machine available for purchase.
GRASS PROTECTION	Pro-Floor® MR can be used for 3-7 days over natural grass surfaces, reducing damage caused by abrasion and wear. Pro-Floor® MR has a moisture containment canopy to prevent burns from severe sunlight. For specific grass protection, we recommend Pro-Floor® GP.
DRAINAGE	Pro-Floor® MR contains in-built grooves and slots to allow water drainage away from the surface reducing the risk of slipping.
USE	This self-supporting, roll-out, portable, slip-resistant flooring system is ideal for the motor industry and can be used in marquees, for pathways and as a portable pit garage floor.